




Anti-Ermüdungsmatte Gripper-Soft



- Lengthwise corrugated rib pattern for sure footing.
- Exceptional worker comfort due to 12,7 mm thick newly formulated compound.
- Protective layer of exclusive Dyna-Shield™ extends service life by 50% compared to regular microcellular vinyl.
- Fire rating Class 2 according NFPA Safety Code 101.
- Available yellow borders along sides comply with OSHA code 1910-144.
- All 4 sides are bevelled and sealed to minimize tripping hazards.
- Free of toxic DOP and DMF.

PRODUCT SPECIFICATIONS		
Designation	Industrial matting	
Type	Anti-fatigue	
Description	Lengthwise corrugated pattern surface, with protective layer of Dyna-Shield™	
Material	Microcellular vinyl	
Process	Foaming	
Category	Better	
Recommended use	Medium duty – dry areas	
Colours	Grey, Black/Yellow, Green	
Weight	4 kg/m ²	
Thickness	12.7 mm	
Standard sizes	60 cm x 91 cm 91 cm x 150 cm 60 cm x 18.3 m 91 cm x 18.3 m 122 cm x 18.3 m	
Custom sizes	60 cm, 91 cm and 122 cm per linear meter	
Special remarks	With Dyna-Shield™, a tough barrier which is 50% more resistant to wear. Ribs are running length-wise.	
PRODUCT TESTING		
Tests	Norms	Results
Compression deflection	U.S.	
	1.4 kg/cm ²	0.62 cm
	2.8 kg/cm ²	0.77 cm
Foam battery	ASTM D3574	40 lb/in ²
Abrasion resistance	ASTM D3884-01	
	500 Cycles	2.15% weight loss
	1000 Cycles	4.9% weight loss
Static coefficient of friction	ASTM C1028-96	1.00
Elongation	ASTM D412	126%
Breaking load	ASTM D412	24.5 lb
Graves tear strength	ASTM D 1004	10.6 lb
Hardness	ASTM D2240-02	15 Shore A
Anti-slip	DIN 51130 and BG-RULE BGR181	
FIRE TESTING		
	Critical radiant flux	ASTM E-648
		0.33 watts/cm ²
	Fire retardancy	DIN4102
		EN 13501-1
	Flammability test	ASTM D2859
		Pass
ESD	ANSI ESD S7.1 50% Humidity	
Sustainability	<ul style="list-style-type: none"> • Recyclable material • Reach Compliant (Registration, Evaluation, Authorization and Restriction of Chemicals) 	

Zu beziehen bei:
 Werkzeug-Profi.net | Matten-Zuschnitt.de
 info@werkzeug-profi.net, 0 63 59/96 11 906