# Sauberlaufmatte für außen, Gripwalk Edge

- Vinyl waves grid matting scrape dirt and moisture off shoes, allowing it to fall in to the mat and not be tracked in to the building (does not absorb water).
- Durable flexible material is ultra violet resistant, performs well in different climates and adapts to any surface.
- The Open wave grid of extruded vinyl creates a slip-resistant walking surface.
- Suitable for heavy traffic conditions.
- Bevelled edges on all four sides prevent tripping on the mat.
- For loose lay.
- Vacuum clean or wash off with hose.
- Free of toxic DOP and DMF.
- Easy to install and relocate. Easy to clean and requires little to no maintenance.
- Suitable for heavy duty use and will not flatten over time.

PRODUCT SPECIFICATIONS	
Designation	Dust Control Matting
Description	Non-absorbent / scrape vinyl mat
Material Top	Open wave design of extruded vinyl
Backing	None
Process	Extrusion
Category	Outdoor Non-absorbent – Grid Matting
Recommended use	In / outdoor - heavy foot traffic
Colours	Grey
Weight	8.5 kg/m^2
Thickness	11 mm
Standard sizes	60 cm x 90 cm 90 cm x 150 cm
Custom sizes	
Special remarks	UV Resistance. Inhibiting to fungal growth in the mat.

PRODUCT TESTING		
Tests	Norms	Results
Abrasion resistance ASTM D3884-01		
Colour fastness to light	ASTM D3884	
Accelerated wear test by sim floor machine	U.S.	
Accelerated soiling	U.S.	
Anti-slip	DIN 51130 and BG-RULE BGR181	
Water retention	U.S.	
Sanitary epidemiologic test	GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV	

FIRE TESTING			
	Surface Flammability	ASTM D2859	
	Classification of the reaction to fire performance	EN 13501-1	
		Pass	
Sustainability	- Recyclable material - Reach Compliant (Registration, Evaluation, Authorization and Restriction of Chemicals) - Contributes to cleaner environment by reducing need of cleaning chemicals		